



### Standard centrifugal pumps

#### **Description**

Lowara CEA series are designed to pump non-aggressive water and clean liquids in agricultural and various industrial applications. These pumps are available in a single phase version (CEAM) and a three phase version (CEA). The CEA series are also available with a pump body entirely made of 316 stainless steel (N-version) to pump aggressive liquids.

#### **Applications**

- o water distribution
- o washing machines
- o reverse osmosis
- o swimming pools
- o circulation of hot and cold liquids

#### **Specifications**

- o suitable for water, clean liquids and continuously duty
- o passes solids: CO350: 11 mm, CO500: 20 mm
- o body: 304 or 316 stainless steel, Viton® FPM O-rings
- o impeller: 304 or 316 stainless steel
- o capacity: up to 31 m³/h
- o head: up to 30 m
- o maximum pressure: 8 bar
- o liquid temperature: max +110 °C
- o standard motor IE2/IE3
- o insulation class: F
- o protection: IP55
- o suction end: 1¼" up to 2"
- o pressure end: 1" and 1¼"
- o motor power P2: up to 3,0 kW
- o single phase version with thermal overload protection
- o power supply:
  - single phase 220-240 Volt 50 Hz (CEAM)
  - three phase 220-240/380-415 Volt 50 Hz
- o available for the North American market on request (cURus)



## Hydraulic performance CEA series at 50 Hz, 2-pole

| PUMP TYPE    | RATED POWER |      | Q = CAPACITY                           |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |     |
|--------------|-------------|------|----------------------------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-----|
|              |             |      | l/min 0                                | 30   | 40   | 60   | 80   | 100  | 120  | 140  | 160  | 180  | 200  | 250  | 300  | 350  | 400  | 430  | 480  | 520 |
|              | m³/h 0      | 1,8  | 2,4                                    | 3,6  | 4,8  | 6    | 7,2  | 8,4  | 9,6  | 10,8 | 12   | 15   | 18   | 21   | 24   | 26   | 29   | 31   |      |     |
|              | kW          | pk   | H=TOTAL HEAD IN METRES COLUMN OF WATER |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |     |
| CEA(M) 70/3  | 0,37        | 0,5  | 22                                     | 20,1 | 19,1 | 16,6 | 12,8 |      |      |      |      |      |      |      |      |      |      |      |      |     |
| CEA(M) 70/5  | 0,55        | 0,75 | 31,1                                   | 28,8 | 27,7 | 24,7 | 20,2 |      |      |      |      |      |      |      |      |      |      |      |      |     |
| CEA(M) 80/5  | 0,75        | 1    | 32                                     | 30   | 29,3 | 27,4 | 24,7 | 21   |      |      |      |      |      |      |      |      |      |      |      |     |
| CEA(M) 120/3 | 0,55        | 0,75 | 22,4                                   |      |      | 18,9 | 17,5 | 15,9 | 14   | 11,8 | 9,2  |      |      |      |      |      |      |      |      |     |
| CEA(M) 120/5 | 0,9         | 1,2  | 31,8                                   |      |      | 28,2 | 26,5 | 24,6 | 22,4 | 20   | 17,3 |      |      |      |      |      |      |      |      |     |
| CEA(M) 210/2 | 0,75        | 1    | 17,7                                   |      |      |      |      |      | 16,5 | 16,1 | 15,6 | 15   | 14,4 | 12,6 | 10,4 |      |      |      |      |     |
| CEA(M) 210/3 | 1,1         | 1,5  | 20,8                                   |      |      |      |      |      | 19,7 | 19,3 | 19   | 18,5 | 18   | 16,5 | 14,4 |      |      |      |      |     |
| CEA(M) 210/4 | 1,5         | 2    | 25,5                                   |      |      |      |      |      | 24,8 | 24,5 | 24   | 23,6 | 23   | 21,3 | 19   |      |      |      |      |     |
| CEA(M) 210/5 | 1,85        | 2,5  | 29                                     |      |      |      |      |      | 28,2 | 27,9 | 27,5 | 27,1 | 26,6 | 25,1 | 23,1 |      |      |      |      |     |
| CEA(M) 370/1 | 1,1         | 1,5  | 16,3                                   |      |      |      |      |      |      |      |      | 15,5 | 15,2 | 14,3 | 13   | 11,4 | 9,4  | 8,1  |      |     |
| CEA(M) 370/2 | 1,5         | 2    | 20,4                                   |      |      |      |      |      |      |      |      |      | 19,1 | 18,3 | 17,2 | 15,8 | 14,1 | 13   | 10,8 |     |
| CEA(M) 370/3 | 1,85        | 2,5  | 24,4                                   |      |      |      |      |      |      |      |      |      | 22,9 | 22,1 | 21,1 | 19,8 | 18,2 | 17,1 | 15   |     |
| CEA370/5     | 3           | 4    | 30,3                                   |      |      |      |      |      |      |      |      |      | 28,3 | 27,5 | 26,5 | 25,3 | 23,8 | 22,8 | 21   |     |

## Electrical motor data CEA series at 50 Hz, 2-pole

| PUMP TYPE    | INPUT POWER* | INPUT CURRENT* | CAPICITOR  |
|--------------|--------------|----------------|------------|
| 1~           | kW           | 220-240 V A    | μF / 450 V |
| CEAM 70/3    | 0,60         | 2,72           | 14         |
| CEAM 70/5    | 0,97         | 4,55           | 16         |
| CEAM 80/5    | 1,07         | 4,87           | 20         |
| CEAM 120/3   | 0,91         | 4,33           | 16         |
| CEAM 120/5   | 1,39         | 6,24           | 25         |
| CEAM 210/2   | 1,13         | 5,10           | 20         |
| CEAM 210/3   | 1,48         | 6,68           | 30         |
| CEAM 210/4   | 1,91         | 8,60           | 40         |
| CEAM 210/5** | 2,24         | 10,2           | 70         |
| CEAM 370/1   | 1,49         | 6,75           | 30         |
| CEAM 370/2   | 2,05         | 9,26           | 40         |
| CEAM 370/3** | 2,45         | 11,1           | 70         |

| PUMP TYPE   | INPUT POWER* | INPUT CURRENT* | INPUT CURRENT |
|-------------|--------------|----------------|---------------|
| 3~          | kW           | 220-240 V A    | 380-415 V A   |
| CEA 70/3    | 0,61         | 2,51           | 1,45          |
| CEA 70/5    | 0,88         | 2,86           | 1,65          |
| CEA 80/5    | 1,06         | 3,65           | 2,11          |
| CEA 120/3   | 0,82         | 2,74           | 1,58          |
| CEA 120/5   | 1,32         | 4,52           | 2,61          |
| CEA 210/2   | 1,12         | 3,76           | 2,17          |
| CEA 210/3   | 1,43         | 4,68           | 2,70          |
| CEA 210/4   | 1,84         | 6,04           | 3,49          |
| CEA 210/5   | 2,28         | 8,35           | 4,82          |
| CEA 370/1   | 1,44         | 4,71           | 2,72          |
| CEA 370/2   | 1,99         | 6,32           | 3,65          |
| CEA 370/3   | 2,47         | 8,63           | 4,98          |
| CEA 370/5** | 3,32         | 10,3           | 5,96          |

\* Maximum value in specific range

\*\* Electric pumps equipped with PLM motor