

ENMIX LIGHT

medium-speed mixer



Agitator mixers

Description

This medium speed mixer is the ideal solution for mixing and motion of fluids in containers and tanks. The mixer can also be used to blend the liquid and to dissolve solid fertilising agents. Various types of mixing tanks are used in modern greenhouse horticulture. The Enmix Light is developed specially for smaller mixing tanks that can contain up to $\pm 2 \text{ m}^3$ with a maximum diameter of 2.5 m. When using larger tanks that can hold up to $\pm 10 \text{ m}^3$ we recommend using the regular Enmix with its more powerful propeller. The Enmix is the perfect alternative for big-bag systems.

The Enmix Light is composed of a four pole motor, with a POM mounting plate for the motor, a 316 stainless steel shaft and a POM stir drive. To ensure an optimal dissolution and sinking particles are thoroughly mixed, propeller must be mounted approximately 10 cm from the bottom. The 316 stainless steel shaft is supplied at a length of 1250 mm as a standard. The shaft is mounted at the end and can be shortened as desired. The electric motor can be connected to a 230 Volt supply. The power of the electric motor is only 0.37 kW.

A simple control box can switch the Enmix Light on and off by pause-pulse timing (is not included). When round tanks are used, two vertical, anti-vortex plates must be fitted inside the tank to prevent the complete volume from whirling. The two anti-vortex plates will cause optimal blending of the liquid. The mixer can also be mounted eccentrically. The objective of the above is to ensure that the fluids are thoroughly mixed. As such, there is an agitator/mixer solution for every fertiliser tank or storage tank.

The Enmix Light mixer is supplied as a single-phase version with a cable, plug and thermal overload protection.

Advantages

- o low energy consumption
- o fits every tank, up to a height of 1400 mm
- o can be mounted easily with motor mounting plate



Technical specifications

- o geared motor:
 - power: 0.37 kW
 - voltage: single-phase 230V
 - frequency: 50/60 Hz motor
 - protection class: IP55
- o mixer:
 - speed: 1350/1580 rpm
- o materials:
 - frame: POM
 - axle: 316 stainless steel
 - mounting plate: POM

UL/CSA certificate on request.

