




Making fresh water possible



Setting new standards for high-pressure pumps – at the heart of seawater RO applications

Fresh, clean water is vital to people everywhere. But access to drinkable water from municipal sources is often prohibitively expensive or simply not an option.

The solution? It is all around us. Brackish water and seawater are abundant, cheap and renewable. But they need to be purified to make drinkable water.

Danfoss Axial Piston Principle (APP) high-pressure pumps are at the heart of more and more small and medium-sized seawater RO applications – because they provide high-pressure reliably and inexpensively.

- 70% of Earth is covered with water
- 97% of this water is seawater
- Only 1% of Earth's water is drinkable
- Worldwide consumption of drinking water doubles every 20 years

Clean water via Reverse Osmosis

Reverse osmosis (RO) has emerged as a preferred method for purifying brackish water and seawater. The process is simple and compact – and requires less energy than other desalination techniques.

While RO is used in massive plants capable of supplying major cities with fresh water, it is also the ideal water purification technique for a host of smaller applications in hotels and resorts, aboard ships and on offshore installations.

The heart of seawater RO systems: Rugged APP high-pressure pumps

Danfoss high-pressure pumps set new standards for small and medium-sized seawater RO applications ranging from 0.6 to 38 m³/h (2.6 to 167 gpm).

Our dedicated high-pressure pumps build on decades of experience in developing pumps for other critical applications. Small in size and unsurpassed in engineering quality, the Danfoss range of high-pressure pumps are at the heart of more than 15,000 seawater RO systems throughout the world.

Cost-efficient Danfoss APP high-pressure pumps function both as main pumps and as reversing pumps (motors) for energy recovery in seawater RO applications.

Dedicated seawater RO pump expertise from a world leader

Danfoss RO Solutions is a division of the Danfoss Group. We and our customers benefit from our close connection to a world leader in development and production of a wide range of mechanical and electronic products and controls. We draw on the extensive Danfoss R&D resources and quality systems, as well as the Group's worldwide manufacturing, distribution and service networks.

We work hard for our growing group of OEM and consulting engineer customers, beginning with extensive pre-sale consultation to determine the right solution for a wide range of seawater RO challenges – and continuing through delivery and uncompromising after-sales support.

APP pump advantages

	Service Life	Efficiency	Pressure Pulsation	Energy Consumption kWh/m³, feed flow. (APP = Index 100)	Total Cost of Ownership, 1 year APP=Index 100	
APP	8,000 hours	> 90 %	< 2%	4.9 (100)	100	
Plunger Pump	1,000 hours	80-85%	15%	5.3 (108)	116	
	(Oil = 500 hours)					
Centrifugal Pump	8,000 hours	50-70%	0%	7.82 (159)	157	

Danfoss APP pumps outperform other pump types

Around the world,
Danfoss RO Solutions provide
OEMs and consulting engineers
with an extensive range of
high-pressure APP pumps for
seawater RO applications.



Flexible and versatile

- The most compact high-pressure pump on the market, with more power per kilo than any other pump
- More design options than with any other RO pump: no need for frames, belt drives or gear boxes – APP pumps can be installed horizontally or vertically
- Wide flow range, with one APP pump covering the range of several centrifugal pumps
- Constant flow regardless of pressure variations

Low maintenance

- Self-lubricating design no need for oil lubricants, ever
 - The pump's only seal is on the mechanical shaft
- All pump parts are made of stainless steel (Duplex or Super Duplex) or polymer
- 8,000 hours maintenance free operation*

Low total costs of ownership

- Ultra-low energy consumption
- Market-leading efficiency: up to 97 % (volumetric) and 93 % (mechanical)
- Permeate cost, with energy recovery, can be reduced to below 2 kWh/m³
- Worldwide support, stock and service networks

^{*} Danfoss guarantees a minimum of 8,000 hours of operation (maximum 18 months from date of production) provided that the pump is used according to Danfoss specifications for pre-filtration, pressure, and rotation speed. Please consult Danfoss RO Solutions for further information.

High-pressure pumps from Danfoss RO Solutions: the right choice wherever fresh water matters








Land based applications

APP high-pressure pumps from Danfoss RO Solutions keep fresh water flowing at hotels, resorts and other installations in coastal regions around the world. APP pumps are suitable for both brackish water (5,000-20,000 ppm/mg/l) and seawater (20,000-50,000 ppm/mg/l).

- Extremely low energy consumption, with up to 97 % efficiency
- Whisper quiet: Danfoss high-pressure pumps are among the most silent in the industry
- Ultra-low maintenance reduces service costs

Pump retrofit cuts energy and maintenance costs at resort

The Challenge: Shangri-La's Mactan Resort and Spa, located on Cebu Island, is the Philippines' premier five-star resort, requiring 1,000 m³ of fresh water per day for its 547 rooms, 7 restaurants and bars, massive pools and spa. When the lush seaside retreat needed to retrofit its old seawater plant, management's main objectives were to reduce energy costs and minimize maintenance.




The Solution: The Danfoss APP21 pump was chosen as the plant workhorse, along with an energy recovery device. Energy consumption was reduced by an impressive 1.7 kWh/m³, which corresponds to yearly savings of € 62,050. Since the self-lubricating APP21 requires no preventive care, maintenance was reduced to a minimum. As an added bonus, noise pollution from the old pump was so radically reduced that the plant is now virtually inaudible from all floors – so guests at Shangri-La's Mactan Resort and Spa can relax more than ever.

Marine and offshore applications

Whether on offshore rigs or aboard private yachts and commercial ships, Danfoss seawater APP pumps are at the heart of seawater RO systems across the seven seas. We have extensive experience in working with OEMs to provide dedicated solutions for small and medium-size applications at sea.

The Royal Navy converts aircraft carrier from flash distillation to RO

The Challenge: HMS Ark Royal is the Royal Navy's largest Invincible-class light aircraft carrier, with a crew of 685 and a Fleet Air Arm of 366. The ship was originally fitted with flash distillers to purify water, but their high energy and maintenance costs led to a conversion to seawater RO in 2005-2006. Salt Separation Services Ltd., who built the new RO plants, wanted to find the right high-pressure pumps for the job.



The solution: Danfoss APP pumps were selected due to their high reliability, low maintenance and small footprint – and are now at the heart of no less than five seawater RO plants aboard HMS Ark Royal: 1×150 m³/day, 2×100 m³/day, and 2×5 m³/day. On the three larger plants, the compact pumps are built into shock-mounted skids so they can easily be routed into position.

- Simple to operate, minimal maintenance, long service life
- Small but effective; light in weight

Mobile and containerized applications

Climate change, natural disasters and humanitarian relief projects often mean that clean drinking water can suddenly become a precious commodity that saves lives. Danfoss RO APP pumps are particularly well suited for small and large-scale mobile applications due to the compact design which is the smallest in the RO market, as well as the extremely high efficiency.

- Small footprint, vertical or horizontal orientation, no belt drive: easy to fit into tight spaces
- No need for oil lubrication, ever.
 8,000 hours maintenance-free operation
- Low vibration means low noise; light in weight
- All pumps can be delivered according to ATEX
- Approved for NATO (N-cage) and specified by military organizations around the world
- Pumps can be made according to API 674 and NORSOK M-650

Wind-driven RO system tested by Dutch university

The challenge: Delft University of Technology wanted to harness a traditional agricultural windmill to drive a RO plant capable of providing fresh water to a village of 500 inhabitants. Despite the need for high-pressure pumping, no electricity would be available to power the pump.



The solution: Researchers chose Danfoss SWPE 1.5-1.2 due to the exceptional energy efficiency of the APP pump and APM energy recovery. But it was the pump's long maintenance-free operation that was particularly appealing for use in remote areas. After successful testing in the Netherlands, the unit was moved to Curacao for operation. The plant is expected to produce 5 m³ of fresh water per day.

An extensive range of high-pressure pumps and accessories to power seawater RO applications

Danfoss RO Solutions develops and markets an extensive range of highpressure pumps and valves. Proven to work in extreme circumstances – and proven to work together.



APP high-pressure pumps

Applications: APP pumps are designed to supply low viscosity and corrosive fluids under high pressure, e.g. in seawater RO applications.

Design: APP pumps are based on the Axial Piston Principle, enabling a very light and compact design. Lubrication of the moving parts in the pumps is provided by the fluid itself, eliminating any need for additional lubrication.

APP pumps are fixed displacement pumps with constant flow, since flow is proportional to input shaft revolutions and pump displacement.

Materials: All pump parts are made of non-corrosive materials, e.g. Duplex and Super Duplex stainless steel and carbon-reinforced PEEK.

APP pumps

Pump type	Flow			Energy consumption	Energy consumption @ 80 bar (1160 psi)	
	rpm	Metric measure	US measure	Metric measure	US measure	Metric measure
APP 0.6	3000	0.6 m³/h	2.6 gpm	1.9 kW	2.5 HP	700-3450 rpm
APP 0.8	3000	0.8 m³/h	3.5 gpm	2.5 kW	3.3 HP	700-3450 rpm
APP 1.0	3000	1.0 m³/h	4.4 gpm	2.9 kW	3.9 HP	700-3450 rpm
APP 1.5	3000	1.5 m³/h	6.6 gpm	4.5 kW	6.0 HP	700-3450 rpm
APP 1.8	3000	1.7 m³/h	7.5 gpm	4.8 kW	6.4 HP	700-3450 rpm
APP 2.2	3000	2.1 m³/h	9.2 gpm	6.0 kW	8.0 HP	700-3450 rpm
APP 2.5	3000	2.6 m³/h	11.4 gpm	7.2 kW	9.6 HP	700-3000 rpm
APP 3.0	3000	3.0 m³/h	13.2 gpm	8.0 kW	10.7 HP	700-3450 rpm
APP 3.5	3000	3.5 m³/h	15.4 gpm	9.3 kW	12.5 HP	700-3000 rpm
APP 5.1	1800	4.9 m³/h	21.6 gpm	13.7 kW	18.4 HP	700-1800 rpm
APP 6.5	1800	6.2 m³/h	27.3 gpm	17.3 kW	23.2 HP	700-1800 rpm
APP 7.2	1800	6.9 m³/h	30.4 gpm	19.2 kW	25.7 HP	700-1800 rpm
APP 8.2	1800	8.2 m³/h	36.1 gpm	21.7 kW	29.1 HP	700-1800 rpm
APP 10.2	1800	10.3 m³/h	45.3 gpm	27.7 kW	37.1 HP	700-1800 rpm
APP 11	1200	11.0 m³/h	48.4 gpm	30.6 kW	41.0 HP	700-1200 rpm
APP 11	1500	11.1 m³/h	48.9 gpm	31.6 kW	42.3 HP	700-1500 rpm
APP 13	1200	13.1 m³/h	57.7 gpm	36.3 kW	48.6 HP	700-1200 rpm
APP 13	1500	13.5 m³/h	59.4 gpm	38.3 kW	51.3 HP	700-1500 rpm
APP 16	1200	16.0 m³/h	70.4 gpm	43.0 kW	58.0 HP	700-1200 rpm
APP 16	1500	15.8 m³/h	69.6 gpm	36.0 kW (70 bar)	48.0 HP	700-1500 rpm
APP 17	1200	17.2 m³/h	75.7 gpm	46.0 kW	62.0 HP	700-1200 rpm
APP 17	1500	16.9 m³/h	74.4 gpm	38.0 kW (70 bar)	51.0 HP	700-1500 rpm
APP 19	1200	18.8 m³/h	82.8 gpm	50.0 kW	67.0 HP	700-1200 rpm
APP 19	1500	18.8 m³/h	82.8 gpm	43.0 kW (70 bar)	58.0 HP	700-1500 rpm
APP 22	1200	21.5 m³/h	94.7 gpm	57.0 kW	76.0 HP	700-1200 rpm
APP 22	1500	21.7 m³/h	95.5 gpm	50.0 kW (70 bar)	67.0 HP	700-1500 rpm
APP 21	1200	20.9 m³/h	92.0 gpm	55.0 kW	73.7 HP	700-1200 rpm
APP 21	1500	21.9 m³/h	96.4 gpm	58.0 kW	77.8 HP	700-1500 rpm
APP 24	1200	24.8 m³/h	109.1 gpm	65.0 kW	87.1 HP	700-1200 rpm
APP 24	1500	24.1 m³/h	106.1 gpm	65.0 kW	87.1 HP	700-1500 rpm
APP 26	1200	26.6 m³/h	117.0 gpm	69.0 kW	92.5 HP	700-1200 rpm
APP 26	1500	26.2 m³/h	115.4 gpm	69.0 kW	92.5 HP	700-1500 rpm
APP 30	1200	30.7 m³/h	135.1 gpm	78.0 kW	104.5 HP	700-1200 rpm
APP 30	1500	31.0 m³/h	136.5 gpm	80.0 kW	107.0 HP	700-1500 rpm
APP 38	1500	38.3 m³/h	168.6 gpm	101.0 kW	135.3 HP	700-1500 rpm

A wide range of filter housings and cartridges for pre-filtration is available.

Sea water pump with energy recovery (SWPE)

Application: The SWPE is a high efficiency energy recovery unit for reverse osmosis filtration of sea water. Energy recovery is achieved by high-pressure brine from membranes being feed into the recovery device (APM) that converts the energy in the pressurized brine to mechanical energy for reuse by the electric motor.



Non-return valves with Vic. ends

Applications: Allow flow in one direction while blocking it in the other.

Design: Conical poppet design, which ensures sealing when used with a low viscosity medium such as seawater.

Capacity: Wide flow range that fits to our pump range.



Design: The SWPE energy recovery unit consists of an APP pump and an APM motor, both connected to a double-shafted electric motor.

The permeate flow and recovery rate depend on the difference between the size of an APP and an APM, as they have a fixed volumetric displacement.

Capacity: SWPE are available in sizes from 4-30 m³/day with recovery rates between 29%-32%. Other sizes are available upon request. Please contact your local Danfoss RO Solutions office.



Danfoss RO Solutions supplies a line of nonreturn valves, Vic. hose connectors, high-pressure hoses, hose tails and Vic. clamps in Duplex.

For more information

For more information on all Danfoss high-pressure pumps, valves and other accessories (including frequency converters, soft starters, high and low-pressure hoses, connections, coupling kits, electrical motors, filters etc.), please visit www.ro-solutions.com.

- · Complete data sheets
- Users' guides & instructions
- References
- Regional sales offices



High-pressure pumps and solutions from a world leader

Danfoss A/S is one of the largest industrial companies in Denmark, with net sales of DKK 33 billion (EUR 4.4 billion). We employ more than 33,000 people, 6,300 of whom work at 15 locations across Denmark.

Danfoss is an international group and a leader in research, development and production for a wide spectrum of different industries.

Danfoss A/S is represented with 61 factories in 25 countries.

The Group's primary aim is to create quality of life for our stakeholders and to be a leader in refrigeration, heating and motion controls.

Our work is based on our core values: Trust, Passion for Technology, Reliability, Global Perspective with Local Commitment, and Environmental and Social Responsibility.



Let us help you optimise your RO project

Our dedicated team of seawater RO experts will be happy to provide design support, technical expertise and customer service. From our headquarters in Denmark or from our worldwide network of subsidiaries, distributors and agents – Danfoss RO Solutions is as close as an e-mail or telephone call.

For more information, please visit www.ro-solutions.com or contact us in Denmark or at one of our regional offices.

 $\textbf{Danfoss A/S RO Solutions} \cdot \textbf{Nordborgvej 81}, \textbf{D25} \cdot \textbf{DK} - \textbf{6430} \cdot \textbf{Nordborg} \cdot \textbf{Denmark} \cdot \textbf{Phone:} + 45\,7488\,4024 \cdot \textbf{Telefax:} + 45\,7445\,3831\,\\ \textbf{Email: ro-solutions@danfoss.com} \cdot \textbf{www.ro-solutions.com}$

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfosss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed.

All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

DKCFN.PB.003.A2.02 - 521B1190 Danfoss A/5 · 09.2012