

TRIPLEX SERIES

PUMP TYPE	MODEL #	MOTOR TYPE	VOLTAGE	PUMP HEAD	ELASTOMERS	FLOW RATE	PRESSURE SWITCH	BYPASS
Standard	T151F-31N7-1P	Permanent magnet DC	12 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	1.5 GPM (5.7 LPM) - Open Flow	No	50 psi (3.4 bar)
Standard	T151F-36N7-1P	Permanent magnet DC	12 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	1.5 GPM (5.7 LPM) - Open Flow	No	50 psi (3.4 bar)
Standard	T151F-71CS-1P	Permanent magnet DC	12 (Vdc)	Glass-filled Nylon	Santoprene diaphragm, EPDM valves	1.5 GPM (5.7 LPM) - Open Flow	100 (psi) 6.9 (bar)	Standard
Standard	T151F-76CS-1P	Permanent magnet DC	12 (Vdc)	Glass-filled Nylon	Santoprene diaphragm, Viton valves	1.5 GPM (5.7 LPM) - Open Flow	100 (psi) 6.9 (bar)	Standard
Standard	T152F-31N7-1P	Permanent magnet DC	24 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	1.5 GPM (5.7 LPM) - Open Flow	No	50 psi (3.4 bar)
Standard	T152F-36N7-1P	Permanent magnet DC	24 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	1.5 GPM (5.7 LPM) - Open Flow	No	50 psi (3.4 bar)
Standard	T152F-71CS-1P	Permanent magnet DC	24 (Vdc)	Glass-filled Nylon	Santoprene diaphragm, EPDM valves	1.5 GPM (5.7 LPM) - Open Flow	100 (psi) 6.9 (bar)	Standard
Standard	T15CF-76CS-1P	Permanent magnet DC	36 (Vdc)	Glass-filled Nylon	Santoprene diaphragm, Viton valves	1.5 GPM (5.7 LPM) - Open Flow	100 (psi) 6.9 (bar)	Standard
Standard	T15FF-31N7-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	1.5 GPM (5.7 LPM) - Open Flow	No	50 psi (3.4 bar)
Standard	T15FF-36N7-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	1.5 GPM (5.7 LPM) - Open Flow	No	50 psi (3.4 bar)
Standard	T15FF-71CS-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Nylon	Santoprene diaphragm, EPDM valves	1.5 GPM (5.7 LPM) - Open Flow	100 (psi) 6.9 (bar)	Standard
Standard	T15FF-76CS-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Nylon	Santoprene diaphragm, Viton valves	1.5 GPM (5.7 LPM) - Open Flow	100 (psi) 6.9 (bar)	Standard
Standard	T15HF-71CS-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Nylon	Santoprene diaphragm, EPDM valves	1.5 GPM (5.7 LPM) - Open Flow	100 (psi) 6.9 (bar)	Standard
Standard	T201F-318S-1P	Permanent magnet DC	12 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	2 GPM (7.6 LPM) - Open Flow	60 (psi) 4.1 (bar)	Standard
Standard	T201F-31N7-1P	Permanent magnet DC	12 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	2 GPM (7.6 LPM) - Open Flow	No	50 psi (3.4 bar)
Standard	T201F-368S-1P	Permanent magnet DC	12 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	60 (psi) 4.1 (bar)	Standard
Standard	T201F-36N7-1P	Permanent magnet DC	12 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	No	50 psi (3.4 bar)
Standard	T202F-318S-1P	Permanent magnet DC	24 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	2 GPM (7.6 LPM) - Open Flow	60 (psi) 4.1 (bar)	Standard
Standard	T202F-368S-1P	Permanent magnet DC	24 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	60 (psi) 4.1 (bar)	Standard
Standard	T202F-76CS-1P:	Permanent magnet DC	24 (Vdc)	Glass-filled Nylon	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	100 (psi) 6.9 (bar)	Standard
Standard	T20FF-318S-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	2 GPM (7.6 LPM) - Open Flow	60 (psi) 4.1 (bar)	Standard

TRIPLEX SERIES

PUMP TYPE	MODEL #	MOTOR TYPE	VOLTAGE	PUMP HEAD	ELASTOMERS	FLOW RATE	PRESSURE SWITCH	BYPASS
Standard	T20FF-368S-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	60 (psi) 4.1 (bar)	Standard
Standard	T20HF-318S-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	2 GPM (7.6 LPM) - Open Flow	60 (psi) 4.1 (bar)	Standard
Standard	T20HF-368S-1P	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	60 (psi) 4.1 (bar)	Standard
Standard	03811033A	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Nylon	Santoprene diaphragm, Viton valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	No
Standard	03811043A	Permanent magnet rectified (PMDC) AC	115 (Vac)	Glass-filled Nylon	Santoprene diaphragm, EPDM valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	No
Standard	R3811133A	Permanent magnet DC	12 (Vdc)	Glass-filled Nylon	Santoprene Diaphragm, Viton Valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	Standard
Standard	R3811143A	Permanent magnet DC	12 (Vdc)	Glass-filled Nylon	Santoprene Diaphragm, EPDM Valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	Standard
Standard	R3811333A	Permanent magnet DC	24 (Vdc)	Glass-filled Nylon	Santoprene Diaphragm, Viton Valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	Standard
Standard	R3811343A	Permanent magnet DC	24 (Vdc)	Glass-filled Nylon	Santoprene Diaphragm, EPDM Valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	Standard
Road Roller	R3B21500A	Permanent magnet DC	12 Volt	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	3.5 GPM (13.2 LPM) - Open Flow	No	50 psi (3.4 bar)
Road Roller	R3B21501A	Permanent magnet DC	24 Volt	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	3.5 GPM (13.2 LPM) - Open Flow	No	50 psi (3.4 bar)
Road Roller	R3B21502A	Permanent magnet DC	12 Volt	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	1.7 GPM (6.4 LPM) - Open Flow	No	50 psi (3.4 bar)
Road Roller	R3B21503A	Permanent magnet DC	24 Volt	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	No	50 psi (3.4 bar)
Road Roller	R3B21507B	Permanent magnet DC	24 Volt	Glass-filled Polypropylene	Santoprene Diaphragm, EPDM Valves	3.5 GPM (13.2 LPM) - Open Flow	No	50 psi (3.4 bar)
Compact	R3501136A	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	60 psi (4.1 bar)	Standard
Compact	R3501146A	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	2 GPM (7.6 LPM) - Open Flow	60 psi (4.1 bar)	Standard
Compact	R3501336A	Permanent Magnet TENV (non-ventilated)	24 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2 GPM (7.6 LPM) - Open Flow	60 psi (4.1 bar)	Standard
Compact	R3501342A	Permanent Magnet TENV (non-ventilated)	24 (Vdc)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	1.4 GPM (5.3 LPM) - Open Flow	60 psi (4.1 bar)	Standard

TRIPLEX SERIES

PUMP TYPE	MODEL #	MAX LIQUID TEMP	DUTY CYCLE	PORT SIZE INLET / OUTLET
Standard	T151F-31N7-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T151F-36N7-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T151F-71CS-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T151F-76CS-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T152F-31N7-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T152F-36N7-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T152F-71CS-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T15CF-76CS-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T15FF-31N7-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T15FF-36N7-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T15FF-71CS-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T15FF-76CS-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T15HF-71CS-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T201F-318S-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T201F-31N7-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T201F-368S-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T201F-36N7-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T202F-318S-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T202F-368S-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T202F-76CS-1P:	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T20FF-318S-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF

TRIPLEX SERIES

PUMP TYPE	MODEL #	MAX LIQUID TEMP	DUTY CYCLE	PORT SIZE INLET / OUTLET
Standard	T20FF-368S-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T20HF-318S-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	T20HF-368S-1P	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	03811033A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	03811043A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	R3811133A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	R3811143A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	R3811333A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Standard	R3811343A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Road Roller	R3B21500A	40°F (4°C) to 140°F (60°C)	Intermittent	Quick-Connect Ports
Road Roller	R3B21501A	40°F (4°C) to 140°F (60°C)	Intermittent	Quick-Connect Ports
Road Roller	R3B21502A	40°F (4°C) to 140°F (60°C)	Intermittent	Quick-Connect Ports
Road Roller	R3B21503A	40°F (4°C) to 140°F (60°C)	Intermittent	Quick-Connect Ports
Road Roller	R3B21507B	40°F (4°C) to 140°F (60°C)	Intermittent	Quick-Connect Ports
Compact	R3501136A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Compact	R3501146A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Compact	R3501336A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF
Compact	R3501342A	40°F (4°C) to 140°F (60°C)	Intermittent	3/8" NPTF