

TRIPLEX SERIES

PUMP TYPE	MODEL #	CE	MOTOR TYPE	VOLTAGE	AMP DRAW	PUMP HEAD	ELASTOMERS	FLOW RATE	PRESSURE SWITCH	BYPASS
Road Roller	na	R3B21501A	Permanent magnet DC	24 Volt	5 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	3.5 GPM (13.2 LPM) - Open Flow	No	50 psi (3.4 bar)
Road Roller	na	R3B21502A	Permanent magnet DC	12 Volt	4 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2.1 GPM (7.9 LPM) - Open Flow	No	50 psi (3.4 bar)
Road Roller	na	R3B21503A	Permanent magnet DC	24 Volt	4 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2.1 GPM (7.9 LPM) - Open Flow	No	50 psi (3.4 bar)
Compact	na	R3501132	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	6 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	1.4 GPM (5.3 LPM) - Open Flow	60 psi (4.1 bar)	40 psi (2.8 bar)
Compact	na	R3501136	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	8 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2.0 GPM (7.9 LPM) - Open Flow	60 psi (4.1 bar)	40 psi (2.8 bar)
Compact	na	R3501142	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	6 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	1.4 GPM (5.3 LPM) - Open Flow	60 psi (4.1 bar)	40 psi (2.8 bar)
Compact	na	R3501146	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	8 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	2.0 GPM (7.9 LPM) - Open Flow	60 psi (4.1 bar)	40 psi (2.8 bar)
Compact	na	R3501332	Permanent Magnet TENV (non-ventilated)	24 (Vdc)	3 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	1.4 GPM (5.3 LPM) - Open Flow	60 psi (4.1 bar)	40 psi (2.8 bar)
Compact	na	R3501336	Permanent Magnet TENV (non-ventilated)	24 (Vdc)	4 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2.0 GPM (7.9 LPM) - Open Flow	60 psi (4.1 bar)	40 psi (2.8 bar)
Compact	na	R3501342	Permanent Magnet TENV (non-ventilated)	24 (Vdc)	3 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	1.4 GPM (5.3 LPM) - Open Flow	60 psi (4.1 bar)	40 psi (2.8 bar)
Compact	na	R3501346	Permanent Magnet TENV (non-ventilated)	24 (Vdc)	4 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	2.0 GPM (7.9 LPM) - Open Flow	60 psi (4.1 bar)	40 psi (2.8 bar)
Compact	03501503	na	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	8 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2.0 GPM (7.9 LPM) - Open Flow	60 psi (4.1 bar)	Yes
Compact	03501506	na	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	8 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2.0 GPM (7.9 LPM) - Open Flow	60 psi (4.1 bar)	Yes
Compact	03B01136	R3B01136	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	8 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	2.0 GPM (7.9 LPM) - Open Flow	No	50 psi (3.4 bar)
Compact	03B01142	R3B01142	Permanent Magnet TENV (non-ventilated)	12 (Vdc)	6 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	1.4 GPM (5.3 LPM) - Open Flow	No	50 psi (3.4 bar)
Compact	na	R3B01332	Permanent Magnet TENV (non-ventilated)	24 (Vdc)	3 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	1.4 GPM (5.3 LPM) - Open Flow	No	50 psi (3.4 bar)
Compact	na	R3B01342	Permanent Magnet TENV (non-ventilated)	24 (Vdc)	3 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	1.4 GPM (5.3 LPM) - Open Flow	No	50 psi (3.4 bar)
High Flow	na	R3521134	Permanent magnet DC	12 (Vdc)	5.2 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	3.0 GPM (11.3 LPM) - Open Flow	50 psi (3.4 bar)	30 psi (2.0 bar)
High Flow	3521139	R3521139	Permanent magnet DC	12 (Vdc)	12 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	4.0 GPM (15.1 LPM) - Open Flow	60 PSI (4.1 bar)	30 psi (2.0 bar)
High Flow	3521149	R3521149	Permanent magnet DC	12 (Vdc)	12 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	4.0 GPM (15.1 LPM) - Open Flow	60 psi (4.1 bar)	30 psi (2.0 bar)
High Flow	na	R3521339	Permanent magnet DC	24 (Vdc)	7 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, Viton valves	4.0 GPM (15.1 LPM) - Open Flow	60 psi (4.1 bar)	30 psi (2.0 bar)
High Flow	na	R3521344	Permanent magnet DC	24 (Vdc)	2.5 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	3.0 GPM (11.3 LPM) - Open Flow	50 psi (3.4 bar)	30 psi (2.0 bar)
High Flow	na	R3521349	Permanent magnet DC	24 (Vdc)	7 (amp)	Glass-filled Polypropylene	Santoprene diaphragm, EPDM valves	4.0 GPM (15.1 LPM) - Open Flow	60 psi (4.1 bar)	30 psi (2.0 bar)
High Pressure	03811133A	R3811133A	Permanent magnet TENV (non-ventilated)	12 (Vdc)	10 (amp)	Glass-filled Nylon	Santoprene Diaphragm, Viton Valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	No
High Pressure	03811143A	R3811143A	Permanent magnet TENV (non-ventilated)	12 (Vdc)	10 (amp)	Glass-filled Nylon	Santoprene Diaphragm, EPDM Valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	No
High Pressure	na	R3811233A	Permanent magnet TENV (non-ventilated)	230 (VAC)	0.6 (amp)	Glass-filled Nylon	Santoprene Diaphragm, Viton Valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	No
High Pressure	03811243A	R3811243A	Permanent magnet TENV (non-ventilated)	230 (VAC)	0.6 (amp)	Glass-filled Nylon	Santoprene Diaphragm, EPDM Valves	1.4 GPM (5.3 LPM) - Open Flow	150 (psi) 10.5 (bar)	No

TRIPLEX SERIES

PUMP TYPE	MODEL #	CE	MAX LIQUID TEMP	DUTY CYCLE	DIMENSIONS (H x W x D)	WEIGHT	CERTIFICATION	PORT SIZE INLET / OUTLET
Road Roller	na	R3B21501A	40°F (4°C) to 160°F (71°C)	Continuous	9.53 x 4.45 x 4.24 (inches) 242.1 x 113 x 107.7 (mm)	3.17 (kg) 7.0 (lb)	CE, RoHS, C-Tick, E-Mark	Quick-Connect Ports
Road Roller	na	R3B21502A	40°F (4°C) to 160°F (71°C)	Continuous	9.53 x 4.45 x 4.24 (inches) 242.1 x 113 x 107.7 (mm)	3.17 (kg) 7.0 (lb)	CE, RoHS, C-Tick, E-Mark	Quick-Connect Ports
Road Roller	na	R3B21503A	40°F (4°C) to 160°F (71°C)	Continuous	9.53 x 4.45 x 4.24 (inches) 242.1 x 113 x 107.7 (mm)	3.17 (kg) 7.0 (lb)	CE, RoHS, C-Tick, E-Mark	Quick-Connect Ports
Compact	na	R3501132	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3501136	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3501142	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3501146	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3501332	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3501336	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3501342	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3501346	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	03501503	na	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	03501506	na	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	03B01136	R3B01136	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	03B01142	R3B01142	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3B01332	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
Compact	na	R3B01342	40°F (4°C) to 140°F (60°C)	Intermittent	8.92 x 3.66 x 3.96 (inches) 227 x 93 x 101 (mm)	1.5 (kg) 3.4 (lb)	CE, NSF components	3/8" NPTF
High Flow	na	R3521134	40°F (4°C) to 140°F (60°C)	Intermittent	9.06 x 4.14 x 4.30 (inches) 230 x 105 x 109 (mm)	2.29 (kg) 5.05 (lb)	CE	Quick-Connect Ports
High Flow	3521139	R3521139	40°F (4°C) to 140°F (60°C)	Intermittent	9.06 x 4.14 x 4.30 (inches) 230 x 105 x 109 (mm)	2.29 (kg) 5.05 (lb)	CE	Quick-Connect Ports
High Flow	3521149	R3521149	40°F (4°C) to 140°F (60°C)	Intermittent	9.06 x 4.14 x 4.30 (inches) 230 x 105 x 109 (mm)	2.29 (kg) 5.05 (lb)	CE	Quick-Connect Ports
High Flow	na	R3521339	40°F (4°C) to 140°F (60°C)	Intermittent	9.06 x 4.14 x 4.30 (inches) 230 x 105 x 109 (mm)	2.29 (kg) 5.05 (lb)	CE	Quick-Connect Ports
High Flow	na	R3521344	40°F (4°C) to 140°F (60°C)	Intermittent	9.06 x 4.14 x 4.30 (inches) 230 x 105 x 109 (mm)	2.29 (kg) 5.05 (lb)	CE	Quick-Connect Ports
High Flow	na	R3521349	40°F (4°C) to 140°F (60°C)	Intermittent	9.06 x 4.14 x 4.30 (inches) 230 x 105 x 109 (mm)	2.29 (kg) 5.05 (lb)	CE	Quick-Connect Ports
High Pressure	03811133A	R3811133A	40°F (4°C) to 140°F (60°C)	Intermittent	10.7 x 3.18 x 3.67 (inches) 256 x 80 x 93 (mm)	3.5 (kg) 7.6 (lb)	CE, NSF components	3/8" NPTF
High Pressure	03811143A	R3811143A	40°F (4°C) to 140°F (60°C)	Intermittent	10.7 x 3.18 x 3.67 (inches) 256 x 80 x 93 (mm)	3.5 (kg) 7.6 (lb)	CE, NSF components	3/8" NPTF
High Pressure	na	R3811233A	40°F (4°C) to 140°F (60°C)	Intermittent	10.7 x 3.18 x 3.67 (inches) 256 x 80 x 93 (mm)	3.5 (kg) 7.6 (lb)	CE, NSF components	3/8" NPTF
High Pressure	03811243A	R3811243A	40°F (4°C) to 140°F (60°C)	Intermittent	10.7 x 3.18 x 3.67 (inches) 256 x 80 x 93 (mm)	3.5 (kg) 7.6 (lb)	CE, NSF components	3/8" NPTF