

JABSCO CYCLONE CENTRIFUGAL PUMPS

MODEL #	CERTIFICATION	VERSION	VOLTAGE	FUSE SIZE	PORT FITTING	OPEN FLOW	MAX PRESSURE	RECOMMENDED DUTY
50840-0012	CE	Low Pressure	12V	10A	3/4" (19mm) NPT	31 GPM (120 LPM)	9 PSI (0.6 BAR)	Continuously rated
50840-0024	CE	Low Pressure	24V	5A	3/4" (19mm) NPT	31 GPM (120 LPM)	9 PSI (0.6 BAR)	Continuously rated
50840-2012	CE	Low Pressure	12V	10A	3/4" (19mm) BSP	31 GPM (120 LPM)	9 PSI (0.6 BAR)	Continuously rated
50840-2024	CE	Low Pressure	24V	5A	3/4" (19mm) BSP	31 GPM (120 LPM)	9 PSI (0.6 BAR)	Continuously rated
50850-0012	CE	Hybrid	12V	7A	3/4" (19mm) NPT	13 GPM (50 LPM)	9 PSI (0.6 BAR)	Continuously rated
50850-2012	CE	Hybrid	12V	7A	3/4" (19mm) BSP	13 GPM (50 LPM)	9 PSI (0.6 BAR)	Continuously rated
50850-2124	CE	Hybrid	24V	5A	3/4" (19mm) BSP	13 GPM (50 LPM)	9 PSI (0.6 BAR)	Continuously rated
50860-0012	CE	High Pressure	12V	25A	3/4" (19mm) NPT	21 GPM (80 LPM)	19 PSI (1.3 BAR)	30 minutes on, 30 minutes off
50860-0024	CE	High Pressure	24V	15A	3/4" (19mm) NPT	21 GPM (80 LPM)	19 PSI (1.3 BAR)	30 minutes on, 30 minutes off
50860-2012	CE	High Pressure	12V	25A	3/4" (19mm) BSP	21 GPM (80 LPM)	19 PSI (1.3 BAR)	30 minutes on, 30 minutes off
50860-2024	CE	High Pressure	24V	15A	3/4" (19mm) BSP	21 GPM (80 LPM)	19 PSI (1.3 BAR)	30 minutes on, 30 minutes off